


R2500E5™ Forced Convection Roaster



- Precision, continuous roasting for a consistent and simplified roasting process
- Efficient, improved energy usage of 7.5kg/kW.h
- Patented roasting process
- Wide range of products
- Forced airflow through the product
- Minimal supervision required whilst roasting continuously
- Gentle mixing of the product during roasting
- Easily accessed to clean inside the machine
- Reliable and safe operation
- Low maintenance cost

Roasting Capacity (Min – Max)	600 – 2500* kg/hr
Electrical Power Consumption (Electrically Heated)	377kW (Roaster only)
Alternative Heat Sources	Diesel/Paraffin
Electrical Power Consumption (Alternative Heat Sources)	18kW (Roaster only) Diesel Consumption: 40 kg/hr
Supply Voltage	Standard: 400Vac, 50Hz, 3Phase
Material	Carbon Steel (Painted) or Stainless Steel(304l/316/3Cr12)
Availability	Commercially 8 – 10 weeks
Application Range	Peanuts/Tree Nuts/Wheat/Soybeans/Coffee Beans/Maize
Weight (Roaster excluding Stand)	2650kg
Size (Roaster excluding Stand)	440cm x 230cm x 210cm

*Maximum roasting capacity based on peanut roasting with an average moisture content of 10%



FORCED CONVECTION CONTINUOUS TUMBLE ROASTING

Mobile +27 82 770 5711
 Fax +27 86 628 4437
 PO Box 31749, Fichardt Park, 9317
 Bloemfontein

C/O Ds Kok & Ds Kotze Street, Ferreira, Bloemfontein, 9300
 Website: www.roastech.com
 E-mail: info@roastech.com
 Republic of South Africa