
R500E5[™] Forced Convection Roaster



- Precision, continuous roasting for a consistent and simplified roasting process
- Efficient, improved energy usage of 7.5kg/kW.h
- Patented roasting process
- Wide range of products
- Forced airflow through the product

- Minimal supervision required whilst roasting continuously
- Gentle mixing of the product during roasting
- Easily accessed to clean inside the machine
- Reliable and safe operation
- Low maintenance cost

Roasting Capacity (Min – Max)	150 – 500* kg/hr
Electrical Power Consumption (Electrically Heated)	85kW
Alternative Heat Sources	Diesel/Paraffin
Electrical Power Consumption (Alternative Heat	9kW (Roaster only)
Sources)	Diesel Consumption: 8 kg/hr
Supply Voltage	Standard: 400Vac, 50Hz, 3Phase
Material	Carbon Steel (Painted) or Stainless Steel (304l/316/3Cr12)
Availability	Commercially 6 – 8 weeks
Application Range	Peanuts/Tree Nuts/Wheat/Soybeans/Coffee Beans/Maize
Weight (Roaster excluding Stand)	850kg
Size (Roaster excluding Stand)	300cm x 140cm x 95cm

*Maximum roasting capacity based on peanut roasting with an average moisture content of 10%



FORCED CONVECTION CONTINUOUS TUMBLE ROASTING

Mobile +27 82 770 5711 Fax +27 86 628 4437 PO Box 31749, Fichardt Park, 9317 Bloemfontein C/O Ds Kok & Ds Kotze Street, Ferreira, Bloemfontein, 9300 Website: www.roastech.com E-mail: info @roastech.com Republic of South Africa